

Specification Date Sheet | Model: 45EB-EU(W)



**ENVIROBULKA 4200 Ltr**

Envirobulka static, 110% bunded fuel tank, built to BS799 Part 5 & to comply with PPG2 Regulations.

- ❖ 110% bunded fuel tank storage tank to comply with PPG2 (Pollution Prevention Guidelines) Regulations.
- ❖ Manufactured to BS799 Part 5- Specification for Oil Storage Tanks.
- ❖ Steel tank enclosed in steel, weatherproof outer bund- robust, durable product providing secure storage.
- ❖ Fitted with lifting eyes and forkliftable base for ease of handing and relocation of tank (empty only)
- ❖ Secure lockable bund compartment houses pump, nozzle, hoses and feed & return connections. Feed & return hoses can be fed through openings enabling generator to be run whilst compartment locked- helps to prevent theft and vandalism.
- ❖ All outlets are mounted above fuel level helping prevent weepage of fuel. Suction pipe to help remove any fluid from the bund.
- ❖ Inspection cover provides access to inner tank for maintenance and inspection.

SPECIFICATION			
Standard Tank Fittings: 2"Vent: 2" Fill Point : 3"Auxiliary Fill Point: 1 x ½" Generator feed: 2 x ½" Return Posts: 1" Pump Feed: Gauge: 2 x 1 ¼" Ports for additional equipment			
Capacity (Brim Full) Litres:	4200	Weight Unladen (kg):	1030
Capacity (Brim Full) Gallons:	923	Weight Laden (kg):	5150*
Dimensions Length (mm):	3100	Design Standards:	PPG2 & PPG2
Dimensions Width (mm):	1200	Cabinet Dimensions (mm) Opening Size: Width 850 x Height 410: Depth 450	
Dimensions Height (mm):	2030		
Notes			
*Specific gravity of diesel taken as 0.9 for this calculation.			

Revision Date: 02/12/2014