



**WACKER  
NEUSON**  
*all it takes!*

## Single direction vibratory plate VP1030A

5000630047

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Plates](#) >> [Single direction Vibratory Plates](#) >> [Single direction vibratory plate VP1030A](#)

### Single direction vibratory plate VP1030A

Material number 5000630047

Single direction vibratory plate for soil compaction



### Product details

#### Compact single direction vibratory plate, for occasional compaction work

- Sturdy design for minimal maintenance effort: The V-belt drive with all-round protection provides for a particularly long operating duration of the V-belt. The base plate is made from wear resistant nodular cast iron.
- A large sturdy lifting eye allows for secure transport. The guide handle that can be folded forward converts the unit into a compact unit in no time

### Comes with

- Single direction vibratory plate for soil compaction
- Operation manual

## Technical specifications

### Single direction vibratory plate VP1030A

#### OPERATING FLUIDS

Tank capacity	0,77 l
---------------	--------

#### ENGINE

Cooling	air cooling
---------	-------------

Engine type	Gasoline engine
-------------	-----------------

Engine operating mode	four-stroke
-----------------------	-------------

Cylinder capacity	121 cm <sup>3</sup>
-------------------	---------------------

Fuel	Gasoline
------	----------

Fuel management	Carburettor
-----------------	-------------

Fuel consumption	0,97 L/Std
------------------	------------

Inclined position max.	20,0 °
------------------------	--------

Cylinder	1
----------	---

Oil specification	SAE 10W-30
-------------------	------------

Oil filling max.	0,40 l
------------------	--------

Power rating max.	2,3 kW
-------------------	--------

Standard (Effective power)	SAE J1349
----------------------------	-----------

Nominal Engine speed	3.600 1/min
----------------------	-------------

Standard (Power max.)	SAE J1349
-----------------------	-----------

Engine speed (Power max.)	3.600 1/min
---------------------------	-------------

Effective power	2,3 kW
-----------------	--------

Oil filling min.	0,40 l
------------------	--------

Exhaust-gas limit	CARB
-------------------	------

Spark plug(s)	NGK CR5HSB
---------------	------------

Starter type	Recoil starter
--------------	----------------

Oil volume incl. filter change	0,40 l
--------------------------------	--------

Air cleaner	dry air filter
Engine Manufacturer	Honda
Electrode distance	0,6 - 0,7 mm

#### Custom Attributes

Model serie	VP
-------------	----

#### Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE